

- PRODUCT NAME** : **RockerKIT PRIMER BRUT Exposed Concrete Primer**
- DESCRIPTION** : Acrylic copolymer based, filler exposed concrete primer for absorbent surfaces.
- INTENDED USES** : Used on interior and exterior applications, exposed concrete surfaces and ceilings.
- PROPERTIES** : Increases adherence before cement and especially gypsum plaster applications.
Prevents rapid water absorption.
Increases the strength of the gypsum plaster.

TECHNICAL DATA :

Appearance	Red or Green
Application temperature	(+5°C) - (+30°C)
Application tools	Application tools
Completely drying time	1-2 hours
Density	1.75±0.05 kg/L
pH	8.5±0.5
Adhesion strength through pull-off test	≥ 0.8 N/mm ²
VOC	<0,01 %

- These values are obtained under laboratory conditions ((23±2) °C temperature, 50% relative humidity) and may differ due to worksite conditions.
- ROCKER YAPI KİM.SAN.TİC.A.Ş. is not responsible for the application errors that may arise if the application conditions and precautions outlined above are not followed for the purpose of the product

SURFACE TREATMENT : The surface should be removed from the unwanted materials such as gypsum, paint, glue, oil and cement residues.

APPLICATION : **RockerKIT PRIMER BRUT** should be applied in as a single layer with a roller, adding up to 20% water and mixing until it becomes homogeneous.
Make sure that the product has completely dried before proceeding to plaster.
If **RockerKIT PRIMER BRUT** will be applied intermittently, it must be mixed again to maintain its homogeneity before each application.
When the primer has dried, a coloured, scratch-free and sandy film layer is obtained.
Application is made on the film layer formed.
Plaster and gypsum application should be started within 3 days at the latest after **RockerKIT PRIMER BRUT** application.

CONSUMPTION : 0,60-0,70 kg/m² (without dilution)
0,35-0,40 kg/m² (diluted 20%)

SHELF LIFE : Shelf life of an unopened package stored in a dry, cool place is 12 months from the date of manufacture. Protect from frost. **RockerKIT PRIMER BRUT** freezes at temperature below 0°C.



TECHNICAL DATA SHEET

PACKAGING : 12 kg Plastic buckets

WARNINGS AND RECOMMENDATIONS :

- The indicated time is valid for 20°C surface and ambient conditions. This time may increase in low temperature and decrease in high temperature.
- For the surface adhesion of the **RockerKIT PRIMER BRUT** product, primer contamination must be prevented during and after the application.
- It should not be used on substrates which have the risk of frost within 24 hours.
- Avoid contact with the skin and should be washed with plenty of water on contact. Appropriate gloves should be used to prevent contact.
- After application, applications tools should be thoroughly washed with water.
- Application in very humid and / or very hot weather should be avoided.
- Structures that are constantly in water are not suitable.

ROCKER YAPI KİMYASALLARI SANAYİ TİCARET A.Ş.

Soğanlık Yeni Mah. Pegagaz Sok. Pega Kartal A Blok Kat : 29 Daire:188 Kartal/İstanbul

Tel : 0850 577 59 56 – 0216 266 85 83

Web : www.rockeryapi.com.tr

e-mail : info@rockeryapi.com.tr